

Mannesmann VDO AG

Kruppstraße 105

60388 Frankfurt

VF42RS/KE-kw

4709

Express Mail mailing label

No. EJ450234790US

Deposited May 31, 2001

5

Description

Electric motor, in particular a fan motor

- TAS*
ai
- Pub.*
B1
- 10 The invention relates to an electric motor having a stator and a rotor, with the rotor having at least one permanent magnet and a rotor shaft and being mounted radially and axially, and with the stator having at least two coils which produce a rotating magnetic field, by means of which the rotor can be driven, when alternating currents flow through them, in particular for use as a blower fan.

- FOR FILING*
- 20 Motors such as these are known from the prior art, whose rotor is produced axially, by means of an axial bearing of the rotor shaft in a sintered bearing. A disadvantage of these motors is that increased wear between the sintered bearing and the rotor shaft initially causes a high level of noise emission, then leading to total failure of the motor. The object of the invention is thus to specify a motor which has a long life while at the same time producing low noise emissions.

- TAS*
ai
- 30 According to the invention, this object is achieved in that the rotor is mounted by means of an elastic thrust ring, with the thrust ring being arranged axially on one side of the rotor. This axial bearing results in permanent axial bearing.
- 35 The motor can be used in any position, if a second elastic thrust ring is arranged axially on the other side of the rotor. Depending on its current position, the rotor can thus load the first or second thrust ring continuously, or the first and second thrust ring alternately. Furthermore, the elasticity of the thrust
- 40

rings prevents impact noise since, when the load on the thrust rings is changed, the elastic thrust rings damp out any striking of the rotor in a sprung manner.

- 5 Elastic thrust rings which are composed of a rubber-like plastic matrix and to one side of which microfibers are applied are particularly preferable. These thrust rings have a particularly long life, since the microfibers do not become detached from the plastic
- 10 matrix. If the microfibers are arranged distributed stochastically on the plastic matrix, this avoids any comb effect even when the motor rotates continuously in one direction.
- 15 The use of a lubricant in the elastic thrust ring results in even lower friction drag on the respective thrust ring, so that the rotor can reach a high rotation speed, thus floating on the elastic thrust ring and hence further reducing the wear coefficients.
- 20 A low-viscosity lubricant is particularly preferable in this case, since this results in particularly lower friction drag on the thrust rings.
- 25 If a recess is formed in the stator in order to accommodate the thrust rings, this makes it possible to reliably prevent lubricant from emerging in specific regions of the motor.
- 30 It is likewise possible to arrange one or more elastic thrust rings in a respective indentation in the rotor. A conical configuration of the recess or indentation in the stator or in the rotor, respectively, makes it possible for the lubricant which emerges from the
- 35 elastic thrust ring when the latter is loaded to gather at points provided for this purpose and to be sucked up from there once again when the load is removed from the elastic thrust ring.

5

10

20

25

25

30

35

If the alternating currents are additionally sinusoidal, this results in the motor running particularly quietly, with little vibration.

5 Its quiet running characteristics mean that the motor described above is particularly suitable for operation as a fan motor with a fan impeller mounted on the rotor shaft.

10 The invention will be explained in more detail in the following text with reference to the figures and for a particularly preferable exemplary embodiment. In the figures:

15 Figure 1 shows a section through a particularly preferred thrust ring

Figure 2 shows a partial section through a particularly preferred rotor

20 Figure 3 shows a view and a partial section of a particularly preferred motor with the fan impeller detached and with a rotor from Figure 2 and thrust rings from Figure 1

Figure 4 shows the partial section A from Figure 3.

25 An elastic thrust ring 1 has a rubber-like plastic matrix 2, composed of soft PVC for example, to one side of which microfibers 3, composed of cut nylon flock for example, are applied which are preferably distributed stochastically. This means that there is no comb effect
30 when they are passed over continuously in one direction. The fibers are repeatedly raised and form small capillaries, which are particularly suitable for absorbing liquids. It is also possible to use a simple felt disk, which may be closed on one side, provided
35 the requirements are not too stringent.

In Figure 2, a rotor 4 has a rotationally symmetrical annular permanent magnet 5, which is connected via a magnet mounting 6 composed of plastic to a rotor shaft

INS
a3

11-11-66

INS
a4
11-11-66
B3

In Figure 3, the rotor 4 from Figure 2 is provided with a fan impeller 9 and is mounted radially in bearing regions 10, 11 of a stator which is designed as a winding body and comprises a winding body upper part 12 and a winding body lower part 13. Axially, the rotor 4 is mounted in a floating manner via two thrust rings 1a, 1b in the indentation 8 in the rotor 4 and in a recess 14 in the winding body lower part 13.

15 The permanent magnet 5 which is embedded in the magnet mounting 6 is pressed onto the rotor shaft 7. A roughened region 15 is applied in the corresponding joint region of the rotor shaft 7, in order to enhance
20 the firm seat. The rotor shaft 7 is polished in regions of the radial mounting 17, 18 in the winding body 12, 13, in order to reduce the friction.

The thrust rings 1a, 1b are arranged in the indentation 8 in the rotor 4 and in the recess 14 in the winding body lower part 13 such that the sides with the microfibers 3a, 3b face the thrust surfaces 6a, 8a formed on the magnet mounting 6 on the rotor 4. The relative movement takes place between the respective fiber side 3a, 3b of the thrust ring 1a, 1b and the rotor 4 with the thrust surfaces 6a, 6b. The thrust rings 1a, 1b are fixed with respect to the stator, which is in the form of the winding bodies 12, 13, when under load. This is achieved by the coefficient of friction between the rubber-like plastic matrix 2 and the stator being higher than that between the microfibers 3 and the rotor 4.

Low-viscosity lubricant is introduced into the fibers of the thrust rings 1a, 1b.

5 The rotor 4 may also be composed completely of magnetic material.

Figure 4 shows a capillary gap 19, which can hold lubricant which is forced out of the thrust ring 1a.

10 The motor can be installed in any desired position, so that, depending on the application, the axial contact force is passed via the thrust ring 1a or 1b into the thrust surface 6a or 8a. If installed horizontally, both thrust rings 1a, 1b are loaded alternately.

15 In order to fit the fan impeller 9 or other functional elements onto the rotor shaft 7 a very high axial force must be applied, once, to the rotor. During this procedure, the thrust ring 1a is compressed until the
20 shaft abuts against a stop 19 which is in the form of a metal ball. Provided it is sufficiently stiff, stop 19 may also be formed from the plastic of the stator, which is in the form of the winding bodies 12, 13. The pressing-on forces are now absorbed by the stop 19, and
25 not by the thrust ring 1a and the magnet mounting 6.

The lubricant which is forced out by the compression can enter the capillary gap 19. Once the pressing-on process has been completed, load is removed from the
30 thrust ring 1a, and the lubricant located in the capillary gap 19 is sucked back into the fibers 3a of the thrust ring 1a.

In the indentation 8, the bearing is protected against
35 loss of lubricant firstly by the capillary effect of the fibers 3b as described above and secondly by the arrangement of the thrust ring 1b in the indentation 8 in the rotor 4. Any lubricant which may emerge due to rotation gathers here in the corner contour of the

- 7 -

indentation 8 and, when the motor is stationary, can migrate back again into the fibers 3b of the thrust ring 1b by virtue of the capillary effect.

5

[illegible]